



2003

Catalog - Division #5
Cisco Cables

Our Cables make "*Right Connection*"
Celebrating our 25th and Silver Anniversary Year of Connectivity

JML Computer Products Incorporated
West Berlin, NJ
USA

In terms of sheer sweep of technological advancement the 25 years since JML began providing custom, state-of-the-art computer interface cables represents an era of unparalleled progress.

This catalog features over 15,000 custom products which we provide today for a constantly expanding base of customers of every size, on six continents.

JML has been presented numerous Supplier Recognition Awards for its excellence in supplying quality products on time with superior service.

Other Divisions of JML Catalog:

- #1) Cables: Network - Voice - Data - Communication - Video - Audio - Telecommunication - Fiber - SCSI - Unisys - HP - IBM
- #2) Cable Adapters: Network - Voice - Communication - Video - Audio - Telecommunication - Fiber - SCSI
- #3) Cabling Equipment: Jacks - Panels - Connectors - Terminators - Racks
- #4) Bulk Cable: Network - Voice - Data - Communication - Video - Audio - Alarm - Telecommunication - Fiber - Underground - Aerial
- #5) Cisco Cables



About Our Part Number

The JML 10 digit part # =
JML Key# + T + L + NNN

T	T Description
A	Adapter
C	Fully Assembled; PVC (CL2)
D	Prepped for conduit; PVC (CL2)
M	Modular Version; PVC(CL2)
P	Fully Assembled; Plenum (CL2P)
R	Prepped for conduit; Plenum (CL2P)
W	Modular Version; Plenum(CL2P)
Y	"Y" Cable; PVC (CL2)

L	L Description
F	FEET
M	METER(S)
N	INCHES
T	THOUSAND FEET
X	Special

NNN
 001 to 999

Examples:

For a **6 inch**, fully assembled, PVC(CL2) rated cable with a JKEY# of **JS132**:
 The JML Part# = **JS132 + (T = C) + (L = N) + (NNN = 006)**
 = **JS132 C N 006**
 = **JS132CN006**

For a **10 foot**, fully assembled, PVC(CL2) rated cable with a JKEY# of **JS111**:
 The JML Part# = **JS111 + (T = C) + (L = F) + (NNN = 010)**
 = **JS111 C F 010**
 = **JS111CF010**

For a **10 meter**, fully assembled, Plenum(CL2P) rated cable with a JKEY# of **JS131**:
 The JML Part# = **JS131 + (T = P) + (L = M) + (NNN = 010)**
 = **JS131 P M 010**
 = **JS131PM010**

For an adapter JKEY# of **JS135**:
 The JML Part# = **JS135 + (T = A) + (L = X) + (NNN = 000)**
 = **JS135 A X 000**
 = **JS135AX000**



About Us

JML can design, build and/or install custom, standard, network and fiber cables for computer and phone systems.

JML builds Copper and Fiber Cables for PC Computer/ Sun/ Unisys/ IBM/ HP/ DEC/ MAC/ Network/ and Mainframe Systems. We can build your cable in any variation and still Ship it in 24 Hours. Each cable is fully tested twice to ensure high quality and long life.

JML cables have a unique serial # which gives them an identity that signifies quality, workmanship, and the honor of a 15 year warranty.

JML has been building Computer Cables since 1979 and along the way our customers have asked us to solve a few of their other communication problems. As a result **JML** can also furnish you with the following products:

- 1) Voice/ Data/ Video infrastructure design, build and service.
- 2) Private Fiber Networks (aerial and underground).
- 3) Documentation, custom cabling and custom solutions for ongoing help desk support and data center moves.
- 4) Authorized dealer/ installer for the top of the line Samsung Telecommunications Business Phone Systems. Digital systems allowing from 3 to 500 users in a single system, with an optional 10/100 Ethernet VoIP port. This port will allow up to 63 of these 500 user systems to talk over a LAN or WAN using the purest form of VoIP available, H.323. Support and service for other systems is also availableavailable.

JML is fully focused on solving the cabling problems of the World. I have 20+ years experience in solving cabling problems and supplying the solution in a timely manner. Call me anytime and I will gladly share my cabling knowledge with you.

Sincerely,

John McLaughlin Jr
President, BSEE, RCDD
800-326-4565 x202



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: 78 PIN CABLE

JML Key #	DESCRIPTION	MODEL
C1321	78-pin D-Shell Cable for CIP (Spare)	CAB-PCA-Y=

CATEGORY: 8 LEAD OCTAL CABLE

JML Key #	DESCRIPTION	MODEL
C1305	8 Lead Octal Cable and 8 Female RS232/V.24 DCE Connectors	CAB-OCT-232-FC=
C1306	8 Lead Octal Cable and 8 Male RS232/V.24 DTE Connectors	CAB-OCT-232-MT=
C1307	8 Lead Octal Cable and 8 Female V35 DCE Connectors	CAB-OCT-V35-FC=
C1308	8 Lead Octal Cable and 8 Male V35 DTE Connectors	CAB-OCT-V35-MT=
C1309	8 Lead Octal Cable and 8 Female X21 DCE Connectors	CAB-OCT-X21-FC=
C1310	8 Lead Octal Cable and 8 Male X21 DTE Connectors	CAB-OCT-X21-MT=
C1311	CABASY, Octopus	CAB-OCT=
C1312	8 Lead Octal Cable (68 pin to 8 Male RJ-45s)	CAB-OCTAL-ASYNC=
C1313	8 Lead Octal Cable and 8 Female DB-25 Terminal Connectors	CAB-OCTAL-FDTE=
C1314	8 Lead Octal Cable and 8 Male DB-25 Modem Connectors	CAB-OCTAL-KIT=
C1315	OCTAL CABLE WITH MALE DB25 CONNECTORS	CAB-OCTAL-MODEM=

CATEGORY: 8 PRI DFC CABLE

JML Key #	DESCRIPTION	MODEL
C1215	1 Meter 8 PRI DFC Cable - Female RJ45	CAB-DFC-OCTAL-1MF=
C1216	1 Meter 8 PRI DFC Cable - Male RJ45	CAB-DFC-OCTAL-1MM=
C1217	2 Meter 8 PRI DFC Cable - Female RJ45	CAB-DFC-OCTAL-2MF=
C1218	2 Meter 8 PRI DFC Cable - Male RJ45	CAB-DFC-OCTAL-2MM=
C1219	3 Meter 8 PRI DFC Cable - Female RJ45	CAB-DFC-OCTAL-3MF=
C1220	3 Meter 8 PRI DFC Cable - Male RJ45	CAB-DFC-OCTAL-3MM=
C1221	.3Meter8PRIDFC Cable-FemaleRJ45	CAB-DFC-OCTAL.3MF=

CATEGORY: ADAPTER CABLE, 75 OHM TO 120OHM



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: ADAPTER CABLE, 75 OHM TO 120OHM

JML Key #	DESCRIPTION	MODEL
C1207	Adapter cable-converts 75 ohm to 120 ohm, Spare	CAB-ADPT-75-120=
C1208	4 pack 75-120 Ohm adapter cables, Spare	CAB-ADPT4P-75-120=

CATEGORY: ADSL CABLE

JML Key #	DESCRIPTION	MODEL
C1210	ADSL cable straight RJ11	CAB-ADSL-RJ11=

CATEGORY: ALARM CABLE

JML Key #	DESCRIPTION	MODEL
C1009	10 Meter Twisted Pair Alarm Cable, HDB-64 -Male,Single Ended	15454E-ALMCBL-010=
C1010	20 Meter Twisted Pair Alarm Cable, HDB-64 -Male,Single Ended	15454E-ALMCBL-020=
C1011	35 Meter Twisted Pair Alarm Cable, HDB-64 -Male,Single Ended	15454E-ALMCBL-035=

CATEGORY: AMP CHAMP CABLE

JML Key #	DESCRIPTION	MODEL
C1001	Cable Assy, AMP-WW, 100 FT	15454-AMP-WW-100=
C1002	Cable Assy, AMP-WW, 250 FT	15454-AMP-WW-250=
C1003	Cable Assy, AMP-WW, 30 FT	15454-AMP-WW-30=
C1004	Cable Assy, AMP-WW, 50 FT	15454-AMP-WW-50=

CATEGORY: ATM CABLE

JML Key #	DESCRIPTION	MODEL
C1212	ATM Cable,DS3+e3;10ft.	CAB-ATM-DS3/E3=
C1213	ATM25 Cable, 96 pin to 4 Male RJ45s (spare)	CAB-ATM25-4=

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: AUX/CONSOLE CABLE

JML Key #	DESCRIPTION	MODEL
C1331	RSM Auxilliary Cable (spare)	CAB-RSM2AUX=
C1332	RSM Console Cable (spare)	CAB-RSM2CON=
C1333	RSP2 Auxiliary Cable (Spare)	CAB-RSP2AUX=
C1334	RSP2 Console Cable (Spare)	CAB-RSP2CON=

CATEGORY: AUX/CONSOLE CABLE KIT

JML Key #	DESCRIPTION	MODEL
C1041	AUX/Console Part Cable Kit	ACS-2500ASYN=
C1042	Auxiliary and Console Port Cable Kit for Cisco 2600 Series	ACS-2600ASYN=
C1043	Auxiliary/Console Port Cable Kit for the Cisco 3600 Series	ACS-3600ASYN=
C1044	Auxiliary/Console Port Cable Kit for the Cisco 7100 Series	ACS-7100ASYN=

CATEGORY: BLUE COLOR DSU/CSU CABLE

JML Key #	DESCRIPTION	MODEL
C1229	Blue Color Cable for DSU/CSU, RJ-45, 6 feet	CAB-DSU-RJ45=

CATEGORY: BUS AND TAG CABLE

JML Key #	DESCRIPTION	MODEL
C1318	Upstream Bus and Tag Connection with Bus and Tag Termination	CAB-PCA-VA=
C1319	Downstream Bus and Tag Connection	CAB-PCA-VB
C1320	Downstream Bus and Tag Connection (78-pin D-Shell Cable to.)	CAB-PCA-VB=

CATEGORY: CAN Cable Extension Kit

JML Key #	DESCRIPTION	MODEL
C1422	CAN Cable Extension Kit	EXT/CAN/15200



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: CATEGORY 3 CABLE AND ADAPTER

JML Key #	DESCRIPTION	MODEL
C1088	Category 3 Telco Cable Adapter (110 Degree)	CAB-3-ADPTR-TEL=
C1089	Category3TelcoCableAssy.M180toF90,10	CAB-3-M180F90-10=
C1090	Category 3 Telco Cable Assy. M180 to F90, 5	CAB-3-M180F90-5=
C1091	Category3TelcoCableAssy.M90toF90,10	CAB-3-M90F90-10=
C1092	Category 3 Telco Cable Assy.M90 to F90,5	CAB-3-M90F90-5=

CATEGORY: CATEGORY 5 TELCO CABLE

JML Key #	DESCRIPTION	MODEL
C1096	Category 5 Telco (RJ-21X) to (12)RJ-45 cable, 10 ft	CAB-5-M120HYD-10=
C1097	Category 5 Telco (RJ-21X) to (12)RJ-45 cable, 5 ft	CAB-5-M120HYD-5=
C1098	Category 5 Telco (RJ-21X) cable, Male-120 to Male-120, 10 ft	CAB-5-M120M120-10=
C1099	Category 5 Telco (RJ-21X) cable, Male-120 to Male-120, 5 ft	CAB-5-M120M120-5=
C1100	Category 5 Telco (RJ-21X) cable, Male-180 to Male-120, 10 ft	CAB-5-M180M120-10=
C1101	Category 5 Telco (RJ-21X) cable, Male-180 to Male-120, 5 ft	CAB-5-M180M120-5=

CATEGORY: CBUS CABLE

JML Key #	DESCRIPTION	MODEL
C1396	CBUS Cable - Male/Female - DB9 Connectors - 0.5m	CBUS-MF-0.5M=
C1397	CBUS Termination - DB9 Connector - 130 Ohm	CBUS-TER=
C1452	Twisted Shielded Pair cable (CBUS) - DB9 Connectors - 1.25m	TSP-1.25M=
C1453	Twisted Shielded Pair cable (CBUS) - DB9 Connectors - 5m	TSP-5M=

CATEGORY: CISCO805 with RS232 Network Cable

JML Key #	DESCRIPTION	MODEL
C1398	CISCO805 with RS232 Network Cable	CISCO805-20PK-232



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: CONSOLE CABLE

JML Key #	DESCRIPTION	MODEL
C1079	Cisco 1600 Console Cable	CAB-1600-CON=
C1336	Supervisor III Console Cable Kit	CAB-S3-CONSOLE
C1394	Cisco 1700 Console Cable	CAB1700-CON=
C1403	CSS11500 Console Cable	CSS5-CON=

CATEGORY: DB 25 ADAPTER

JML Key #	DESCRIPTION	MODEL
C1316	DB25 Female DTE Adapter	CAB-OTF=
C1317	DB25 Male DTE Adapter	CAB-OTM=

CATEGORY: DB 25/RJ45 ADAPTER

JML Key #	DESCRIPTION	MODEL
C1163	ADP,RJ45/DSUB,MODEM	CAB-5MODCM

CATEGORY: DB15 Y CABLE

JML Key #	DESCRIPTION	MODEL
C1108	DB15/Y Cable /M15-F15 10ft	CAB-5607-10=

CATEGORY: DB15-RJ48 CABLE

JML Key #	DESCRIPTION	MODEL
C1337	DA-15 Female-to-RJ-48 Male Cable, 7.5 Meters	CAB-SDS0=

CATEGORY: DB15-RJ48C CONNECTOR



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: DB15-RJ48C CONNECTOR

JML Key #	DESCRIPTION	MODEL
C1234	DB15 to RJ48C for connecting AS5200 E1 as Network Terminal	CAB-E1-PRI/NT=

CATEGORY: DB25 ADAPTER

JML Key #	DESCRIPTION	MODEL
C1303	DB25 Female DCE Adapter	CAB-OCF=
C1304	DB25 Male DCE Adapter	CAB-OCM=

CATEGORY: DB25 TO RJ45 CONNECTOR

JML Key #	DESCRIPTION	MODEL
C1102	DB-25 Female DCE to RJ-45 Connector	CAB-500DCF=
C1103	DB-25 Male DCE to RJ-45 Connector	CAB-500DCM=
C1104	DB-25 Female DTE to RJ-45 Connector	CAB-500DTF=
C1105	DB-25 Male DTE to RF-45 Connector	CAB-500DTM=

CATEGORY: DB25-RJ45 CABLE

JML Key #	DESCRIPTION	MODEL
C1330	Eight RJ45 to DB25 cables for the AS25XX-RJ	CAB-RJ-MODEM-8=

CATEGORY: DHEI CABLE

JML Key #	DESCRIPTION	MODEL
C1164	DHEI Input Cables, spare	CAB-6920-DHEI-IN=
C1165	DHEI Output Cable, spare	CAB-6920-DHEI-OUT=

CATEGORY: E1 120 OHM CABLE



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: E1 120 OHM CABLE

JML Key #	DESCRIPTION	MODEL
C1012	10 Meter E1 cable, 120Ohm Twisted Pr, DB37-Male, Single Ended	15454E-DBCBL-010=
C1013	20 Meter E1 cable, 120Ohm Twisted Pr, DB37-Male, Single Ended	15454E-DBCBL-020=
C1014	35 Meter E1 cable, 120Ohm Twisted Pr, DB37-Male, Single Ended	15454E-DBCBL-035=

CATEGORY: E1 75 OHM CABLE

JML Key #	DESCRIPTION	MODEL
C1018	10 Meter E1/E3/DS3 cable, 75 Ohm T54 connector, Single Ended	15454E-T54CBL-010=
C1019	20 Meter E1/E3/DS3 cable, 75 Ohm T54 connector, Single Ended	15454E-T54CBL-020=
C1020	35 Meter E1/E3/DS3 cable, 75 Ohm T54 connector, Single Ended	15454E-T54CBL-035=

CATEGORY: E1 CABLE

JML Key #	DESCRIPTION	MODEL
C1156	E1/BNC to BNC Cable 10 Feet	CAB-5697-10=
C1231	E1 Cable, BNC E1, 75ohm/Unbalanced, 3 Meters	CAB-E1-BNC-3M
C1232	FSIP and MIP-CE1: BNC 75ohm/Unbal 5 meters	CAB-E1-BNC=
C1233	E1 Cable DB15 120 ohm/Balanced, 5 meters	CAB-E1-DB15=
C1235	E1 ISDN PRI CABLE, 10 FOOT	CAB-E1-PRI=
C1236	E1 Cable RJ45 to dual BNC (unbalanced), Spare	CAB-E1-RJ45BNC=
C1237	Spare E1 Cable RJ45 to RJ45 TE	CAB-E1-RJ45TE=
C1238	E1 Cable RJ45 to Twinax (balanced), Spare	CAB-E1-RJ45TWIN=
C1239	E1 Cable Twinax 120ohm/Balanced 3 Meters	CAB-E1-TWINAX-3M
C1240	FSIP and MIP-CE1: TWINAX 120ohm/Bal 5m	CAB-E1-TWINAX=

CATEGORY: E1 Y CABLE

JML Key #	DESCRIPTION	MODEL
C1146	E1 / Y Cable 10 ft	CAB-5685-10=

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: E2000/APC FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1404	Optical Patchcord - E2000/APC Connectors - 0.5m	E2000-APC-0.5M=
C1405	Optical Patchcord - E2000/APC Connectors - 0.75m	E2000-APC-0.75M=
C1406	Optical Patchcord - E2000/APC Connectors - 1.25m	E2000-APC-1.25M=
C1407	Optical Patchcord - E2000/APC Connectors - 1.5m	E2000-APC-1.5M=
C1408	Optical Patchcord - E2000/APC Connectors - 10m	E2000-APC-10M=
C1409	Optical Patchcord - E2000/APC Connectors - 20m	E2000-APC-20M=
C1410	Optical Patchcord - E2000/APC Connectors - 3m	E2000-APC-3M=
C1411	Optical Patchcord - E2000/APC Connectors - 5m	E2000-APC-5M=
C1412	Optical Patchcord - E2000/APC Connectors - 2dB Attenuation	E2000-E2000-2DB=
C1413	Optical Patchcord - E2000/APC Connectors - 3dB Att. - 0.5m	E2000-E2000-3DB.5=
C1414	Optical Patchcord - E2000/APC Connectors - 5dB Att. - 0.5m	E2000-E2000-5DB.5=
C1415	Optical Patchcord - E2000/APC Connectors - 5dB Attenuation	E2000-E2000-5DB=
C1416	Optical Patchcord - E2000/APC Connectors - 7dB Att. - 0.5m	E2000-E2000-7DB.5=
C1417	Optical Patchcord - E2000/APC Connectors - 7dB Attenuation	E2000-E2000-7DB=
C1418	Optical Patchcord - E2000/APC Connectors - 8dB Attenuation	E2000-E2000-8DB=
C1419	Optical Patchcord - E2000/APC Connectors - 9dB Att. - 0.5m	E2000-E2000-9DB.5=
C1420	Optical Patchcord - E2000/APC Connectors - 9dB Attenuation	E2000-E2000-9DB=

CATEGORY: E2000/APC FIBER COUPLER

JML Key #	DESCRIPTION	MODEL
C1421	Double Fiber Coupler - E2000/APC Connectors	E2000-E2000ADAPT=

CATEGORY: ETHERNET ADAPTER CABLE

JML Key #	DESCRIPTION	MODEL
C1093	18 Inch Ethernet Adaptor Cable	CAB-3CE18=

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: ETHERNET BNC CABLE

JML Key #	DESCRIPTION	MODEL
C1072	Ethernet Cable - BNC Connectors - 10m	BNC-10M=
C1073	Ethernet Coaxial Cable - BNC / BNC Connectors - 12.5 Meter	BNC-12.5M=
C1074	Ethernet Coaxial Cable - BNC / BNC Connectors - 2.5 Meter	BNC-2.5M=
C1075	Ethernet Cable - BNC Connectors - 20m	BNC-20M=
C1076	Ethernet Cable - BNC Connectors - 5m	BNC-5M=
C1077	Ethernet Coaxial Cable - BNC / BNC Connectors - 7.5 Meter	BNC-7.5M=

CATEGORY: ETHERNET BNC TERMINATOR

JML Key #	DESCRIPTION	MODEL
C1078	Ethernet Termination - BNC Connector - 50 Ohm	BNC-TER=

CATEGORY: ETHERNET CABLE

JML Key #	DESCRIPTION	MODEL
C1241	Yellow Cable for Ethernet, Straight-through, RJ-45, 6 feet	CAB-ETH-S-RJ45=
C1242	Ethernet Cross-over Cable	CAB-ETHXOVER=

CATEGORY: ETHERNET SMA CABLES AND ADAPTERS

JML Key #	DESCRIPTION	MODEL
C1446	Ethernet Cable - SMA Connectors - 1m	SMA-1M=
C1447	Ethernet Adaptor - SMA / DIN Connectors	SMA-DIN-ADP=
C1448	Ethernet T - SMA Connectors	SMA-T=

CATEGORY: FC-FC SM FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1338	100ft Single Mode Fiber Cable (FC term.)	CAB-SMF-FC-100=



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: FC-FC SM FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1339	10ft Single Mode Fiber Cable (FC term.)	CAB-SMF-FC-10=
C1340	25ft Single Mode Fiber Cable (FC term.)	CAB-SMF-FC-25=
C1341	50ft Single Mode Fiber Cable (FC term.)	CAB-SMF-FC-50=
C1342	75ft Single Mode Fiber Cable (FC term.)	CAB-SMF-FC-75=

CATEGORY: FC-FC SM Y CABLE

JML Key #	DESCRIPTION	MODEL
C1348	Single Mode Fiber Y Cable (FC Term)	CAB-SMF-Y-FC=

CATEGORY: FC-PC ATTENUATOR

JML Key #	DESCRIPTION	MODEL
C1055	Optical Attenuator - FC-PC Connectors - 10dB Attenuation	ATT-FC-PC-10DB=
C1056	Optical Attenuator - FC-PC Connectors - 15dB Attenuation	ATT-FC-PC-15DB=
C1057	Optical Attenuator - FC-PC Connectors - 20dB Attenuation	ATT-FC-PC-20DB=
C1058	Optical Attenuator - FC-PC Connectors - 2dB Attenuation	ATT-FC-PC-2DB=
C1059	Optical Attenuator - FC-PC Connectors - 3dB Attenuation	ATT-FC-PC-3DB=
C1060	Optical Attenuator - FC-PC Connectors - 5dB Attenuation	ATT-FC-PC-5DB=
C1061	Optical Attenuator - FC-PC Connectors - 7dB Attenuation	ATT-FC-PC-7DB=
C1062	Optical Attenuator - FC-PC Connectors - 9dB Attenuation	ATT-FC-PC-9DB=

CATEGORY: FC-PC FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1423	Optical Patchcord - FC-PC Connectors - 0.75m	FC-PC-0.75=
C1429	Optical Patchcord - FC-PC Connectors - 2m	FC-PC-2=
C1430	Optical Patchcord - FC-PC Connectors - 3.5m	FC-PC-3.5=
C1432	Optical Patchcord - FC-PC Connectors - 5m	FC-PC-5=



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: FC-UPC FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1424	Optical Patchcord - FC-PC Connectors - 0.75m 5dB Attenuation	FC-PC-0.75M-5DB=
C1425	Optical Patchcord - FC-UPC Connectors - 10m	FC-PC-10=
C1426	Optical Patchcord - FC-UPC Connectors - 15m	FC-PC-15=
C1427	Optical Patchcord - FC-UPC Connectors - 20m	FC-PC-20=
C1428	Optical Patchcord - FC-UPC Connectors - 25m	FC-PC-25=
C1431	Optical Patchcord - FC-UPC Connectors - 30m	FC-PC-30=

CATEGORY: FIBER TOKEN RING CABLE

JML Key #	DESCRIPTION	MODEL
C1457	1 Meter Cable WS-X5031 Token Ring Fiber Cat5000 Module	WS-CAB01ST=
C1458	3 Meter Cable WS-X5031 Token Rng Fiber Cat5000 Module	WS-CAB03ST=
C1459	8 Meter ST Cable For Cat 5000 Fiber TR Switch Module	WS-CAB08ST=

CATEGORY: FIBRE CHANNEL CABLE

JML Key #	DESCRIPTION	MODEL
C1449	SFP,FIBRE CH MM OR GIGABIT W/LC CONNECTOR, SPARE	SN-SFP-FCGEMM-LC=
C1450	SFP, FIBRE CHANNEL MM W/LC CONNECTOR	SN-SFP-FCMM-LC

CATEGORY: GBIC CABLE

JML Key #	DESCRIPTION	MODEL
C1244	1 meter cable for GigaStack GBIC	CAB-GS-1M
C1245	50 centimeter cable for GigaStack GBIC	CAB-GS-50CM

CATEGORY: GIGABIT CABLE



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: GIGABIT CABLE

JML Key #	DESCRIPTION	MODEL
C1451	SFP,GIGABIT W/MTRJ CONNECTOR	SN-SFP-GEMM-MTRJ

CATEGORY: H.100 DROP CABLE

JML Key #	DESCRIPTION	MODEL
C1454	12 Drop PCI Cable	UNITY-CTBUS-12=
C1455	4 Drop H.100 PCI Voice Board Connector Cable	UNITY-CTBUS-4=
C1456	8 Drop H.100 PCI Voice Board Connector Cable	UNITY-CTBUS-8=

CATEGORY: HSSI CABLE

JML Key #	DESCRIPTION	MODEL
C1269	HSSI Cable, Male-to-Male Null Modem Cable, 10 Feet	CAB-HNUL=
C1270	HSSI Null Modem Cable for UFM-U and FRSM-HS1	CAB-HS1-DTE=
C1271	HSSI Cable, Male-to-Male Connectors, 10 Feet	CAB-HS1=

CATEGORY: IGX-UFM-U CABLE

JML Key #	DESCRIPTION	MODEL
C1084	Cable for IGX-UFM-U 2 Port V35 Cable (Female DCE)	CAB-2V35FC=
C1085	Cable for IGX-UFM-U 2 Port V35 Cable (Male DTE)	CAB-2V35MT=
C1086	Cable for IGX-UFM-U 2 Port X21 Cable (Female DCE)	CAB-2X21FC=
C1087	Cable for IGX-UFM-U 2 Port X21 Cable (Male DTE)	CAB-2X21MT=

CATEGORY: IGX-UFM-U Y CABLE

JML Key #	DESCRIPTION	MODEL
C1392	Y-Cable for IGX-UFM-U HSSI	CAB-Y-HS1=

CATEGORY: IP/VC CABLE



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: IP/VC CABLE

JML Key #	DESCRIPTION	MODEL
C1272	IP/VC V.35/RS-366 Video Terminal Adapter Cable-DCE	CAB-IPVC-V35-DCE=
C1273	IP/VC V.35/RS-366 Gateway Cable-DTE	CAB-IPVC-V35-DTE=
C1274	IP/VC 3510/20/25/30 Accessory Cable Kit	CAB-IPVC3500-KIT
C1275	IP/VC 3540 Accessory Cable Kit	CAB-IPVC3540-KIT

CATEGORY: LC-LC MM FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1282	Multi mode - LC cable	CAB-MMF-LC=
C1400	CSS11500 10-Meter Fiber Multimode SX LC Connectors	CSS5-CABSX-LC=

CATEGORY: LC-LC SM CABLE

JML Key #	DESCRIPTION	MODEL
C1352	Single Mode IR LC cable	CAB-SMFIR-LC=

CATEGORY: LC-LC SM Y CABLE

JML Key #	DESCRIPTION	MODEL
C1350	Single Mode IR LC - Y cable	CAB-SMFIR-LC-Y
C1351	Single Mode IR LC - Y cable	CAB-SMFIR-LC-Y=

CATEGORY: LC-SC MM FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1401	CSS11500 10-Meter Fiber Multimode SX LC-to-SC Connectors	CSS5-CABSX-LCSC
C1402	CSS11500 10-Meter Fiber Multimode SX LC-to-SC Connectors	CSS5-CABSX-LCSC=

CATEGORY: LC-SC SM FIBER CABLE



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: LC-SC SM FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1399	CSS11500 10-Meter Fiber Single Mode LX LC-to-SC Connectors	CSS5-CABLX-LCSC=

CATEGORY: LR-LC SM CABLE

JML Key #	DESCRIPTION	MODEL
C1353	Single Mode LR LC - Y cable	CAB-SMFLR-LC-Y
C1354	Single Mode LR LC - Y cable	CAB-SMFLR-LC-Y=
C1355	Single Mode LR - LC Cable	CAB-SMFLR-LC=

CATEGORY: MC3810 E AND M CROSS OVER CABLE

JML Key #	DESCRIPTION	MODEL
C1230	MC3810 EandM Cross-over Cable for TBR-17 Compliance	CAB-E&;M-TBR17

CATEGORY: MINI DIN -DIN CONVERTER CABLE

JML Key #	DESCRIPTION	MODEL
C1243	Cisco 7000 Series Mini DIN-to-DIN Converter Cable (Spare)	CAB-FMDD=

CATEGORY: MIP-CT1 CABLE

JML Key #	DESCRIPTION	MODEL
C1178	MIP-CT1: DSX1 to CSU DB-15 Thru Cable	CAB-7KCT1DB15=
C1179	MIP-CT1: DSX1 to CSU DB-15 Null Cable	CAB-7KCT1NULL=

CATEGORY: MM Y CABLE



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: MM Y CABLE

JML Key #	DESCRIPTION	MODEL
C1036	50/125um Multimode Y Cable with SC for Channel Protection	15500-CAB-YMM-SC=

CATEGORY: MMF-SMF CABLE

JML Key #	DESCRIPTION	MODEL
C1280	10 feet MMF-SMF Cable (FC and SC term, 10 dB Atten.)	CAB-MM-SM-SCFC=
C1281	MMF-SMF Long Reach Cable (FC and SC term, 15 dB Atten.)	CAB-MM-SMLR-SCFC=

CATEGORY: MODEM CONNECTOR

JML Key #	DESCRIPTION	MODEL
C1083	Male DB-25 Modem Connector	CAB-25AS-MMOD=

CATEGORY: MTP CABLE

JML Key #	DESCRIPTION	MODEL
C1031	2.5m (86 in.) MTP to MTP cable	15500-CAB-MTP-01=
C1032	MTP to 8-MU optical cable - Mux/Demux to CC Drawer - Color	15500-CAB-MTPMU-M=

CATEGORY: MTRJ-SC MM FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1289	MT-RJ MM to SC Duplex MM - 1 meter	CAB-MTRJ-SC-MM-1M=
C1290	MT-RJ MM to SC Duplex MM - 3 meter	CAB-MTRJ-SC-MM-3M=
C1291	MT-RJ MM to SC Duplex MM - 5 meter	CAB-MTRJ-SC-MM-5M=
C1292	MT-RJ MM to ST Duplex MM - 1 meter	CAB-MTRJ-ST-MM-1M=
C1293	MT-RJ MM to ST Duplex MM - 3 meter	CAB-MTRJ-ST-MM-3M=
C1294	MT-RJ MM to ST Duplex MM - 5 meter	CAB-MTRJ-ST-MM-5M=

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: MU ADAPTER

JML Key #	DESCRIPTION	MODEL
C1033	ONS 15540 ESPx - MU-MU Insertion Adaptor	15500-CAB-MU-ADTR=

CATEGORY: MU ATTENUATOR

JML Key #	DESCRIPTION	MODEL
C1071	8dB Attenuator, MU Connector, 15200	ATTEN/MU/8/15200=

CATEGORY: MU-MU CABLE

JML Key #	DESCRIPTION	MODEL
C1022	0.35m (14 in.) Tuned Low Loss MU-MU SM OADM Patch Cable	15500-CAB-MMU-02=
C1023	0.45m (17 in.) Tuned Low Loss MU-MU SM OADM Patch Cable	15500-CAB-MMU-03=
C1024	0.5m (20 in.) Tuned Low Loss MU-MU SM OADM Patch Cable	15500-CAB-MMU-04=
C1025	1.0m (40 in.) Tuned Low Loss MU-MU SM OADM Patch Cable	15500-CAB-MMU-05=
C1026	1.5m (60 in.) Tuned Low Loss MU-MU SM OADM Patch Cable	15500-CAB-MMU-06=
C1027	2.0m (79 in.) Tuned Low Loss MU-MU SM OADM Patch Cable	15500-CAB-MMU-07=
C1028	2.5m (98 in.) Tuned Low Loss MU-MU SM OADM Patch Cable	15500-CAB-MMU-08=
C1029	1.0m Tuned Low Loss MU to SC SM Patch Cable	15500-CAB-MS01=
C1030	3.0m Tuned Low Loss MU to SC SM Patch Cable	15500-CAB-MS02=

CATEGORY: NI-2 CABLE

JML Key #	DESCRIPTION	MODEL
C1214	NI-2 Console Cable - Spare	CAB-CON-NI=



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: OC48/SRP CABLE

JML Key #	DESCRIPTION	MODEL
C1395	Coax mate cable for OC48/SRP	CBL-SRP-OC48=

CATEGORY: ONS FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1433	Optical Cable - For ONS 15808 SHELF-MUX - 10 Meter	OPT-CBL-MUX-10M=
C1434	Optical Cable - For ONS 15808 SHELF-MUX - 20 Meter	OPT-CBL-MUX-20M=
C1435	Optical Cable - For ONS 15808 SHELF-MUX - 5 Meter	OPT-CBL-MUX-5M=
C1436	Optical Cable - For ONS 15808 SHELF-TXT - 10 Meter	OPT-CBL-TXT-10M=
C1437	Optical Cable - For ONS 15808 SHELF-TXT - 20 Meter	OPT-CBL-TXT-20M=
C1438	Optical Cable - For ONS 15808 SHELF-TXT - 5 Meter	OPT-CBL-TXT-5M=

CATEGORY: ORANGE ISDN CABLE

JML Key #	DESCRIPTION	MODEL
C1335	Orange Color Cable for ISDN BRI S/T, RJ-45, 6 feet	CAB-S/T-RJ45=

CATEGORY: POWER CABLE

JML Key #	DESCRIPTION	MODEL
C1000	Two Conductor AC Power Cable, North America	15201-PWR-CBL-NA=
C1015	10Meter, 8 AWG, 3 conductor, Single Ended Power Cable	15454E-PWRCBL-010=
C1016	20Meter, 8 AWG, 3 conductor Single Ended Power Cable	15454E-PWRCBL-020=
C1017	35Meter, 8 AWG, 3 conductor Single Ended Power Cable	15454E-PWRCBL-035=
C1021	North America	15500-CAB-AC=
C1038	Custom AC Power Entry Cable	15540-CAB-AC=
C1158	IGX/All,IPX16/32 Power Cord w/CE 23-16/VII plug-Italy	CAB-590071=
C1159	IGX/All,IPX16/32 Power Cord w/CEE 7/7 plug-Europe	CAB-590072=
C1160	IGX/All,IPX16/32 Power Cord w/AS3112 plug-Aust and N Zealand	CAB-590073=
C1161	IGX/All,IPX 16/32 Power Cord w/BS 1363 plug-G.B and Ireland	CAB-590074=
C1162	IGX/All,IPX16/32 Pwr Cd w/NEMA L6-20 Twistlock plug-NA / JP	CAB-590076=

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: POWER CABLE

JML Key #	DESCRIPTION	MODEL
C1166	Cisco 7513 Series AC Power Cord 208V Twist-Lock, US	CAB-7513AC-208VTL=
C1167	Cisco 7513 Series AC Power Cord Twist-Lock, US	CAB-7513AC-TL=
C1168	AC POWER CORD NORTH AMERICA	CAB-7513AC=
C1169	AC POWER CORD (EUROPE)	CAB-7513ACE=
C1170	AC POWER CORD (UK)	CAB-7513ACU=
C1171	AC Power Cord North America, 15A - spare	CAB-7KAC-15=
C1172	Cisco 7500 Series AC Power Cord, US	CAB-7KAC=
C1173	Cisco 7500 Series AC Power Cord, Australia	CAB-7KACA=
C1174	Cisco 7500 Series AC Power Cord, Europe	CAB-7KACE=
C1175	Cisco 7500 Series AC Power Cord CD12, Italy	CAB-7KACI=
C1176	AC Power Cord (South Africa) Spare	CAB-7KACSA=
C1177	Cisco 7500 Series AC Power Cord, UK	CAB-7KACU=
C1180	Power Cord for North America, 125VAC/13A	CAB-AC-125V/13A=
C1181	Power Cord, 250Vac 16A, Europe	CAB-AC-2500W-EU=
C1182	Power Cord, 250Vac 16A, INTL	CAB-AC-2500W-INT=
C1183	Power Cord, 250Vac 16A, straight blade NEMA 6-20 plug, US	CAB-AC-2500W-US1=
C1184	Power Cord for North America, 250VAC/13A	CAB-AC-250V/13A=
C1185	Europe Power Cord	CAB-AC-2800W-EU=
C1186	International Power Cord	CAB-AC-2800W-INT=
C1187	U.S. Power Cord, Twist Lock, NEMA 6-20 Plug	CAB-AC-2800W-TWLK=
C1188	Power Cord, 250Vac 16A, twist lock NEMA L6-20 plug, US	CAB-AC-C6K-TWLK=
C1189	Y power cord US, for use with 5300 redundant power supply	CAB-AC-Y-AS=
C1190	Spare 10A AC Pwr Cord, left-angle (Australia)	CAB-AC10A-90L-AU=
C1191	Spare 10A AC Pwr Cord, left-angle (Europe)	CAB-AC10A-90L-EU=
C1192	Spare 10A AC Pwr Cord, left-angle (Italy)	CAB-AC10A-90L-IT=
C1193	Spare 10A AC Pwr Cord, left-angle (UK)	CAB-AC10A-90L-UK=
C1194	Spare 15A AC Pwr Cord, left-angle (US)	CAB-AC15A-90L-US=
C1195	AC Power Cord, US	CAB-AC=
C1196	Y power cord AUS, for use w/ 5300 redundant power supply	CAB-ACA-Y-AS=
C1197	AC Power Cord, Australia	CAB-ACA=
C1198	Y power cord EUR, for use w/ 5300 redundant power supply	CAB-ACE-Y-AS=
C1199	AC Power Cord, Europe	CAB-ACE=
C1200	Y power cord Italy, for use with 5300 redundant power supply	CAB-ACI-Y-AS=
C1201	AC Power Cord, Italy	CAB-ACI=
C1202	Y power cord Argentina used with 5300 redundant power supply	CAB-ACR-Y-AS=
C1203	Power Cord Argentina, Spare	CAB-ACR=

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: POWER CABLE

JML Key #	DESCRIPTION	MODEL
C1204	Power cord for Switzerland (spare)	CAB-ACS=
C1205	Y power cord UK, for use with 5300 redundant power supply	CAB-ACU-Y-AS=
C1206	AC Power Cord, UK	CAB-ACU=
C1222	Cisco 120 VAC Power Cable, US	CAB-DS-120VAC=
C1223	Cisco 6400 250 VAC Power Cable, USA	CAB-DS-250VAC=
C1224	Power Cables for AC Power Option, Australian	CAB-DS-ACA
C1225	Power Cables for AC Power Option, European	CAB-DS-ACE
C1226	Power Cables for AC Power Option, Italian	CAB-DS-ACI
C1227	Power Cables for AC Power Option, Japan	CAB-DS-ACJ-TWLK
C1228	Power Cables for AC Power Option, UK	CAB-DS-ACU
C1246	Cisco 12012 GSR AC Power Supply Cord, Australia	CAB-GSR12-AU=
C1247	Cisco 12012 GSR AC Power Supply Cord, Europe	CAB-GSR12-EU=
C1248	Cisco 12012 GSR AC Power Supply Cord, Italy	CAB-GSR12-IT=
C1249	Cisco 12012 GSR AC Power Supply Cord, UK	CAB-GSR12-UK=
C1250	Cisco 12012 GSR AC Power Supply Cord, US	CAB-GSR12-US=
C1251	Cisco 12016 GSR AC Power Supply Cord, Australia Spare	CAB-GSR16-AU=
C1252	Cisco 12016 GSR AC Power Supply Cord, Europe Spare	CAB-GSR16-EU=
C1253	Cisco 12016 GSR AC Power Supply Cord, Italy Spare	CAB-GSR16-IT=
C1254	Cisco 12016 GSR AC Power Supply Cord, UK Spare	CAB-GSR16-UK=
C1255	Cisco 12016 GSR AC Power Supply Cord, US Spare	CAB-GSR16-US=
C1256	Cisco 12404 220VAC Power Supply Cord, US	CAB-GSR4-220V-US=
C1257	Cisco 12406 220VAC Power Supply Cord, US	CAB-GSR6-220V-US=
C1258	Cisco 12406 GSR AC Power Supply Cord, Australia	CAB-GSR6-AU=
C1259	Cisco 12406 GSR AC Power Supply Cord, Europe	CAB-GSR6-EU=
C1260	Cisco 12406 GSR AC Power Supply Cord, Italy	CAB-GSR6-IT=
C1261	Cisco 12406 GSR AC Power Supply Cord, UK	CAB-GSR6-UK=
C1262	Cisco 12406 GSR AC Power Supply Cord, US	CAB-GSR6-US=
C1263	Cisco 12008 GSR AC Power Supply Cord, Australia	CAB-GSR8-AU
C1264	Cisco 12008 GSR AC Power Supply Cord, Australia	CAB-GSR8-AU=
C1265	Cisco 12008 GSR AC Power Supply Cord, Europe	CAB-GSR8-EU=
C1266	Cisco 12008 GSR AC Power Supply Cord, Italy	CAB-GSR8-IT=
C1267	Cisco 12008 GSR AC Power Supply Cord, UK	CAB-GSR8-UK=
C1268	Cisco 12008 GSR AC Power Supply Cord, US	CAB-GSR8-US=
C1276	Power Cord-Japan	CAB-JPN=
C1295	Power Cable for AC Power Option - Argentina	CAB-NP1200-AC-AR=
C1296	Power Cable for AC Power Option - Australia/NZ	CAB-NP1200-AC-AU=
C1297	Power Cable for AC Power Option, China	CAB-NP1200-AC-CH=
C1298	Power Cable for AC Power Option - European	CAB-NP1200-AC-EU=
C1299	Power Cable for AC Power Option - Italian	CAB-NP1200-AC-IT=
C1300	Power Cable for AC Power Option, Japan	CAB-NP1200-AC-JP=
C1301	Power Cable for AC Power Option - UK	CAB-NP1200-AC-UK=

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: POWER CABLE

JML Key #	DESCRIPTION	MODEL
C1302	Power Cable for AC Power Option, North America	CAB-NP1200-AC-US=
C1322	Spare Japan Power Cable LRE 575 CPE	CAB-PS-LRE-JPN=
C1323	Cisco Two Conductor AC Power Cable ARG	CAB-PWR-2WIRE-ARG=
C1324	Cisco Two Conductor AC Power Cable AUS	CAB-PWR-2WIRE-AUS=
C1325	Cisco Two Conductor AC Power Cable EU	CAB-PWR-2WIRE-EU=
C1326	Cisco Two Conductor AC Power Cable KOR	CAB-PWR-2WIRE-KOR=
C1327	Cisco Two Conductor AC Power Cable NA	CAB-PWR-2WIRE-NA=
C1328	Cisco Two Conductor AC Power Cable UK	CAB-PWR-2WIRE-UK=
C1439	Power Cord with AS 3112 plug (Australia and New Zealand)	PWRCD-ANZ=
C1440	Power Cord with CEE 7/7 plug (Continental Europe)	PWRCD-EU=
C1441	Power Cord with BS 1363 plug (Great Britain and Ireland)	PWRCD-GBI=
C1442	Power Cord with CEI 23-16/VII plug (Italy)	PWRCD-IT=
C1443	Power Cord with NEMA L6-20 Twistlock plug (North America and	PWRCD-NA=

CATEGORY: Posi-Lok SMB to BNC Adaptor Cable

JML Key #	DESCRIPTION	MODEL
C1375	Posi-Lok SMB to BNC 12 Adaptor Cables Bundle for UXM-T3/E3	CAB-T3E3-PL-AD-12=
C1376	Posi-Lok SMB to BNC 16 Adaptor Cables Bundle for BXM-T3/E3	CAB-T3E3-PL-AD-16=
C1377	Posi-Lok SMB to BNC 24 Adaptor Cables Bundle for BXM-T3/E3	CAB-T3E3-PL-AD-24=
C1378	Posi-Lok SMB to BNC 6 Adaptor Cables Bundle for UXM-T3/E3	CAB-T3E3-PL-AD-6=
C1379	Posi-Lok SMB to BNC Adaptor Cable for BXM-T3/E3	CAB-T3E3-PL-AD=
C1380	Posi-Lok SMB to BNC 12 Y Cables Bundle for UXM-T3/E3	CAB-T3E3-PL-Y-12=
C1381	Posi-Lok SMB to BNC 16 Y Cables Bundle for BXM-T3/E3	CAB-T3E3-PL-Y-16=
C1382	Posi-Lok SMB to BNC 24 Y Cables Bundle for BXM-T3/E3	CAB-T3E3-PL-Y-24=
C1383	Posi-Lok SMB to BNC 6 Y Cables Bundle for UXM-T3/E3	CAB-T3E3-PL-Y-6=
C1384	Posi-Lok SMB to BNC Y Cable for BXM-T3/E3	CAB-T3E3-PL-Y=

CATEGORY: RED ISDN CABLE



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: RED ISDN CABLE

JML Key #	DESCRIPTION	MODEL
C1385	Red Color Cable for ISDN BRI U, RJ-45, 6 feet	CAB-U-RJ45=

CATEGORY: RJ45-RJ45 CABLE

JML Key #	DESCRIPTION	MODEL
C1106	RJ-45 to RJ-45 Cable, 14 Feet	CAB-500RJ=

CATEGORY: RJ45-RJ45 FEMALE ADAPTERS

JML Key #	DESCRIPTION	MODEL
C1209	8 Female RJ-45 to Female RJ-45 Adapters	CAB-ADPTRS-RJ45=

CATEGORY: RJ48-RJ48 CABLE

JML Key #	DESCRIPTION	MODEL
C1147	ASSY CBL RJ48(M) to RJ48(F) Y CABLE, 4	CAB-5686-04=
C1148	ASSY CBL RJ48(M) to RJ48(F) Y CABLE, 6	CAB-5686-06=
C1149	ASSY CBL DB15(M) to RJ48(F)	CAB-5687-06=
C1150	ASSY CBL DB15(M) to RJ48(F)	CAB-5687-08=
C1151	ASSY CBL RJ48(M) TO DB9(F), 6	CAB-5688-06=
C1152	ASSY CBL RJ48(M) TO DB9(F), 18	CAB-5688-18=
C1153	ASSY CBL RJ48(M) TO DB9(F)	CAB-5689-06=
C1154	ASSY CBL RJ48(M) TO DB9(F)	CAB-5689-18=

CATEGORY: RP-TNC CABLE

JML Key #	DESCRIPTION	MODEL
C1051	20 ft LOW LOSS CABLE ASSEMBLY W/RP-TNC CONNECTORS	AIR-CAB020LL-R
C1052	50 ft. LOW LOSS CABLE ASSEMBLY W/RP-TNC CONNECTORS	AIR-CAB050LL-R
C1053	100 ft. ULTRA LOW LOSS CABLE ASSEMBLY W/RP-TNC CONNECTORS	AIR-CAB100ULL-R

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: RP-TNC CABLE

JML Key #	DESCRIPTION	MODEL
C1054	150 ft. ULTRA LOW LOSS CABLE ASSEMBLY W/RP-TNC CONNECTORS	AIR-CAB150ULL-R

CATEGORY: RP-TNC CONNECTOR

JML Key #	DESCRIPTION	MODEL
C1047	RP-TNC Male Connector for 9913 Cable	AIR-ACC1622
C1048	RP-TNC Female Connector for 9913 Cable	AIR-ACC1623
C1049	RP-TNC Male Connector for RG-58 Cable	AIR-ACC1655
C1050	RP-TNC Female Connector for RG-58 Cable	AIR-ACC1828

CATEGORY: RS-232 CABLE

JML Key #	DESCRIPTION	MODEL
C1080	RS-232 Cable, DCE, Female, 10 Feet	CAB-232FC=
C1081	RS-232 Cable, DTE, Male, 10 Feet	CAB-232MT=
C1121	RS232/M25 - F25 10 Feet	CAB-5620-10=
C1122	RS232/M25 - F25 25 ft	CAB-5620-25=
C1123	RS232/M25 - M25/Special 100 Feet	CAB-5621-00=
C1124	RS232/M25 - M25/Special 10 Feet	CAB-5621-10=
C1125	RS232/M25 - M25/Special 25 Feet	CAB-5621-25=
C1127	RS232/M15 - F25 10 Feet	CAB-5625-10=
C1128	RS232/M15 - F25 25 Feet	CAB-5625-25=
C1129	RS232/M15 - F25 50 Feet	CAB-5625-50=
C1130	RS232/M15 - M25 10 Feet	CAB-5626E-10=
C1131	RS232/M15 - M25 25 Feet	CAB-5626E-25=
C1132	RS232/M15 - M25 50 Feet	CAB-5626E-50=
C1329	RS-232 Cable, Female-to-Male Connectors, 3 Meters	CAB-R23=
C1356	RS-232 Cable, DCE Female to Smart Serial, 10 Feet	CAB-SS-232FC=
C1357	RS-232 Cable, DTE Male to Smart Serial, 10 Feet	CAB-SS-232MT=

CATEGORY: RS-232 Y CABLE

JML Key #	DESCRIPTION	MODEL
C1126	RS232/Y Cable/M25 - F25 (RS232/Y) 10 Feet	CAB-5624-10=

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: RS-232 Y CABLE

JML Key #	DESCRIPTION	MODEL
C1133	RS232/Y Cable/M15 - F15 (LDI/Y) 10 Feet	CAB-5629-10=

CATEGORY: RS-422 Y CABLE

JML Key #	DESCRIPTION	MODEL
C1138	RS422/Y Cable (RS422/Y) 10 Feet	CAB-5644-10=

CATEGORY: RS-449 CABLE

JML Key #	DESCRIPTION	MODEL
C1094	RS-449 Cable, DCE, Female, 10 Feet	CAB-449FC=
C1095	RS-449 Cable, DTE, Male, 10 Feet	CAB-449MT=
C1139	RS449DTE(M) TO X.21/V.11DTE(F) 10 Feet	CAB-5645-10=
C1140	RS449DCE(M) TO X.21/V.11DCE(F) 10 Feet	CAB-5646-10=
C1358	RS-449 Cable, DCE Female to Smart Serial, 10 Feet	CAB-SS-449FC=
C1359	RS-449 Cable, DTE Male to Smart Serial, 10 Feet	CAB-SS-449MT=

CATEGORY: RS-530 CABLE

JML Key #	DESCRIPTION	MODEL
C1107	Male DTE RS-530 Cable, 10 foot	CAB-530MT=
C1361	RS-530 Cable, DTE Male to Smart Serial, 10 Feet	CAB-SS-530MT=

CATEGORY: RS-530A CABLE

JML Key #	DESCRIPTION	MODEL
C1360	RS-530A Cable, DTE Male to Smart Serial, 10 Feet	CAB-SS-530AMT=

CATEGORY: SC-FC ADAPTER



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: SC-FC ADAPTER

JML Key #	DESCRIPTION	MODEL
C1045	Optical Adapter - SC-FC Connectors - Single Fiber	ADP-SC-FC=
C1046	Optical Adapter - SC-SC Connectors - Single Fiber	ADP-SC-SC=

CATEGORY: SC-PC ATTENUATOR

JML Key #	DESCRIPTION	MODEL
C1063	Optical Attenuator - SC-PC Connectors - 10dB Attenuation	ATT-SC-PC-10DB=
C1064	Optical Attenuator - SC-PC Connectors - 15dB Attenuation	ATT-SC-PC-15DB=
C1065	Optical Attenuator - SC-PC Connectors - 20dB Attenuation	ATT-SC-PC-20DB=
C1066	Optical Attenuator - SC-PC Connectors - 2dB Attenuation	ATT-SC-PC-2DB=
C1067	Optical Attenuator - SC-PC Connectors - 3dB Attenuation	ATT-SC-PC-3DB=
C1068	Optical Attenuator - SC-PC Connectors - 5dB Attenuation	ATT-SC-PC-5DB=
C1069	Optical Attenuator - SC-PC Connectors - 7dB Attenuation	ATT-SC-PC-7DB=
C1070	Optical Attenuator - SC-PC Connectors - 9dB Attenuation	ATT-SC-PC-9DB=

CATEGORY: SC-SC MM FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1034	1.0m SC to SC 62.5 mic MM Patch Cable	15500-CAB-SC11=
C1283	100 feet Multi-Mode Fiber Cable (SC term.)	CAB-MMF-SC-100=
C1284	10 feet Multi-Mode Fiber Cable (SC term.)	CAB-MMF-SC-10=
C1285	25 feet Multi-Mode Fiber Cable (SC term.)	CAB-MMF-SC-25=
C1286	50 feet Multi-Mode Fiber Cable (SC term.)	CAB-MMF-SC-50=
C1287	75 feet Multi-Mode Fiber Cable (SC term.)	CAB-MMF-SC-75=

CATEGORY: SC-SC MM FIBER Y CABLE

JML Key #	DESCRIPTION	MODEL
C1288	Multi-Mode Y Cable, SC Connectors, Only One Allowed per Path	CAB-MMF-Y-SC=

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: SC-SC SM FIBER CABLE

JML Key #	DESCRIPTION	MODEL
C1035	1.0m SC to SC SM Patch Cable	15500-CAB-SC12=
C1343	100 feet Single-Mode Fiber Cable (SC term.)	CAB-SMF-SC-100=
C1344	10 feet Single-Mode Fiber Cable (SC term.)	CAB-SMF-SC-10=
C1345	25 feet Single-Mode Fiber Cable (SC term.)	CAB-SMF-SC-25=
C1346	50 feet Single-Mode Fiber Cable (SC term.)	CAB-SMF-SC-50=
C1347	75 feet Single-Mode Fiber Cable (SC term.)	CAB-SMF-SC-75=

CATEGORY: SC-SC SM Y CABLE

JML Key #	DESCRIPTION	MODEL
C1349	Single Mode Fiber Y Cable (SC Term)	CAB-SMF-Y-SC=

CATEGORY: SCSI CABLE

JML Key #	DESCRIPTION	MODEL
C1211	8 ft long SCSI-II cable for AIC	CAB-AIC-008=
C1444	1 meter SCSI cable - 68 pin, spare	SCSI-CABLE-1M=
C1445	3 meter SCSI cable - 68 pin, spare	SCSI-CABLE-3M=

CATEGORY: SM Y CABLE

JML Key #	DESCRIPTION	MODEL
C1037	Single Mode Y Cable with SC for Channel Protection	15500-CAB-YSM-SC=

CATEGORY: SMB CABLE

JML Key #	DESCRIPTION	MODEL
C1277	Miniature SMB T3/E3 cable	CAB-MCC-T3E3
C1279	Miniature SMB T3/E3 cable	CAB-MCC-T3E3=



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: SMB Y CABLE

JML Key #	DESCRIPTION	MODEL
C1278	Miniature SMB T3/E3 - Y cable	CAB-MCC-T3E3-Y=

CATEGORY: SMB-BNC CABLE

JML Key #	DESCRIPTION	MODEL
C1005	Cable Assy, SMB-BNC, 10 FT	15454-SMB-BNC-10=
C1006	Cable Assy, SMB-BNC, 30 FT	15454-SMB-BNC-30=
C1007	Cable Assy, SMB-BNC, 50 FT	15454-SMB-BNC-50=
C1008	Cable Assy, SMB-BNC, 75 FT	15454-SMB-BNC-75=
C1039	Cable pair SMB to BNC - female -spare	2CBLE-SMB-BNC-F=
C1040	Cable pair SMB to BNC - male - spare	2CBLE-SMB-BNC-M=
C1145	ASSY CBL SMB(M) TO BNC(F), 6	CAB-5682-06=

CATEGORY: SMB-BNC Y CABLE

JML Key #	DESCRIPTION	MODEL
C1144	ASSY CBL SMB(M) to BNC(F) Y CABLE, 5.5	CAB-5681-06=

CATEGORY: T1 CABLE

JML Key #	DESCRIPTION	MODEL
C1109	T1/Pigtail - RJ48 10 Feet	CAB-5608-10=
C1110	T1/M15 - Pigtail 100 Feet	CAB-5611-00=
C1111	T1/M15 - Pigtail 25 Feet	CAB-5611-25=
C1112	T1/M15 - Pigtail 50 Feet	CAB-5611-50=
C1113	T1/M15 - M15 Xover 100 Feet	CAB-5614-00=
C1114	T1/M15 - M15 Xover 10 Feet	CAB-5614-10=
C1115	T1/M15 - M15 Xover 25 Feet	CAB-5614-25=
C1116	T1/M15 - M15 Xover 50 ft	CAB-5614-50=
C1117	T1/M15 - M15 100 Feet	CAB-5616-00=
C1118	T1/M15 - M15 10 Feet	CAB-5616-10=
C1119	T1/M15 - M15 25 Feet	CAB-5616-25=
C1120	T1/M15 - M15 50 Feet	CAB-5616-50=
C1141	T1/F15 - RJ48 10 Feet	CAB-5680-10=

JML Computer Products Incorporated ● 1019 Industrial Drive ● West Berlin, NJ 08091

ph: 856.753.8500 ● 800.326.4JML(4565) ● fax: 856.753.0355 ● Sales@JMLCable.com ● JMLCable.com



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: T1 CABLE

JML Key #	DESCRIPTION	MODEL
C1142	T1/M15 - RJ48 25 Feet	CAB-5680-25=
C1143	T1/F15 - RJ48 50 Feet	CAB-5680-50=
C1368	T1 Cable RJ45 to RJ45 Bare, Spare	CAB-T1-RJ45BARE=

CATEGORY: T3/E3 CABLE

JML Key #	DESCRIPTION	MODEL
C1369	T3/E3 Interface Coax Cable 100 Feet	CAB-T3-E3-00=
C1370	T3/E3 Interface Coax Cable 10 Feet	CAB-T3-E3-10=
C1371	T3/E3 Interface Coax Cable 25 Feet	CAB-T3-E3-25=
C1372	T3/E3 Interface Coax Cable 50 Feet	CAB-T3-E3-50=
C1373	T3/E3 Interface Coax Cable 75 Feet	CAB-T3-E3-75=

CATEGORY: T3/E3 SMB-SMB Posi-Lock CABLE

JML Key #	DESCRIPTION	MODEL
C1157	T3/E3 SMB to SMB Posi-Lok Cable 6 Feet	CAB-5698-6=

CATEGORY: T3/E3 Y CABLE

JML Key #	DESCRIPTION	MODEL
C1374	T3/E3 Y Cable	CAB-T3-E3-Y=

CATEGORY: TERMINAL CONNECTOR

JML Key #	DESCRIPTION	MODEL
C1082	Female DB-25 Terminal Connector	CAB-25AS-FDTE=

CATEGORY: UFM-U Y CABLE



Division #5) Cisco Cables

JML Part# = JKEY# + T + L + NNN = JKEY#TLNNN = 10 Digits
 L = F(feet), I(inches), M(meters), T(thousands of feet) / NNN = 001 to 999

CATEGORY: UFM-U Y CABLE

JML Key #	DESCRIPTION	MODEL
C1393	Y-Redundancy Cable for UFM-U (V.35 or X.21)	CAB-Y-UF1=

CATEGORY: V.35 CABLE

JML Key #	DESCRIPTION	MODEL
C1134	V.35/M34 - F34 100 Feet	CAB-5630-00=
C1135	V.35/M34 - F34 10 Feet	CAB-5630-10=
C1136	V.35/M34 - F34 25 Feet	CAB-5630-25=
C1137	V.35/M34 - F34 50 Feet	CAB-5630-50=
C1362	V.35 Cable, DCE Female to Smart Serial, 10 Feet	CAB-SS-V35FC=
C1363	V.35 Cable, DTE Female to Smart Serial, 10 Feet	CAB-SS-V35FT=
C1364	V.35 Cable, DCE Male to Smart Serial, 10 Feet	CAB-SS-V35MC=
C1365	V.35 Cable, DTE Male to Smart Serial, 10 Feet	CAB-SS-V35MT=
C1386	V.35 Cable, DCE, Female, 10 Feet	CAB-V35FC=
C1387	V.35 Cable, DTE, Female, 10 Feet	CAB-V35FT=
C1388	V.35 Cable, DCE, Male, 10 Feet	CAB-V35MC=
C1389	V.35 Cable, DTE, Male, 10 Feet	CAB-V35MT=

CATEGORY: X.21 CABLE

JML Key #	DESCRIPTION	MODEL
C1366	X.21 Cable, DCE Female to Smart Serial, 10 Feet	CAB-SS-X21FC=
C1367	X.21 Cable, DTE Male to Smart Serial, 10 Feet	CAB-SS-X21MT=
C1390	X.21 Cable, DCE, Female, 10 Feet	CAB-X21FC=
C1391	X.21 Cable, DTE, Male, 10 Feet	CAB-X21MT=

CATEGORY: X.21 Y CABLE

JML Key #	DESCRIPTION	MODEL
C1155	X.21 Trunk - Y Cable (DB15) 10 Feet	CAB-5695-10=